

FAAST SAMPLING HOLE IDENTIFICATION SYSTEM

Aspirating Smoke Detection

When installing an Aspirating Smoke Detection (ASD) systems in large format applications like warehouses or big open spaces with high ceilings, commissioning and installation time can be increased if the right approach is not employed. When dealing with such applications, it is often almost impossible to identify the exact location of sampling holes and more importantly, identify if the sampling hole is the correct size, creating unnecessary delays.

Honeywell's CLIP Hole Identification system is designed to alleviate such potential issues, by providing a clear, visual indication of sampling point location and its associated hole size. Each CLIP is colour-coded and indicates a specific hole diameter, providing an instantly accessible visual guide that can ease the installation process as well as help service engineers and auditors to update or test the system more efficiently.

Sampling hole creation is also greatly simplified using this technology; a 12mm diameter drill is all that is required by an installer to create each sampling hole (rather than many different drill sizes).

Another key benefit of using Honeywell's CLIP Hole Identifiers is the inclusion of a chamfered hole entry in the clip design; an aspect which is proven to significantly reduce dust loading effects. Without using this type of technology, a build-up of dust around a standard drilled sampling hole is likely to occur, due to the static energy created by the airflow through the sampling hole. By reducing dust loading effects and leveraging the additional protection provided by CLIP Hole Identifiers, sites can help to increase system uptime and potentially extend service and testing intervals.

Unlike most contemporary solutions, the Honeywell CLIP Hole Identification System is installation-ready (with no need for assembly, any additional parts or tools); CLIPs are provided as a single ready-to-fit piece. Honeywell's CLIPS are also available in two formats; Standard and Harsh Environments. Harsh environment CLIP variants feature a flexi-lip design that changes its shape when subjected to blow off pressure. This ensures that any ice, fiber or dust build-up on the supporting rubber structure can be easily detached and broken up by the air Jetstream out of the CLIP hole, providing additional protection in challenging locations like freezer applications.



Standard CLIPS

Harsh Environment CLIPS

ASD CLIPS FEATURES

- Two versions available: Standard and Harsh Environments
- Clear and easily accessible visual colour-coded guide to sample hole location and sampling hole size; even in the largest format applications
- Installation-ready design (with no part assembly or tools required); each CLIP simply clicks into place for a firm, non-slip position
- Greatly simplifies sample hole drilling; a single 12mm drill can be used to create all holes (simply fit the relevant CLIP to limit the hole size after initial hole drilling)
- Harsh Environment CLIPS feature a flexi-lip that can adapt to any changes caused by environmental fluctuations including freezing; any dust, ice or fiber will detach and break apart easily, ensuring even air flow sampling in all conditions
- Reduces dust loading effects through inclusion of a chamfered hole
- Permits faster, more efficient commissioning and installation, as well as ongoing maintenance


ASD CLIPS TECHNICAL SPECIFICATIONS

Easy-fit CLIP Functionality

Step 1: Simply use a 12mm drill bit to create all sample holes

Step 2: Fit the relevant colour-coded CLIP; place over the hole and secure in place by applying pressure until a “click” occurs.

- CLIPS are available ready-to-fit
- No part assembly required; one single system
- No special tools required
- Added durability through a flexi-lip design (Harsh Environment CLIPs), that changes its shape when subjected to blow off pressure. This prevents ice, dust or fiber build up on the supporting rubber structure, by allowing it to be detached by the air jetstream out of the CLIP hole
- CLIPS do not slip and stay firmly in place due to easy click-fit technology
- Anti-pressure shock design that is ideal for automatic purge systems



PERFORMANCE SPECIFICATION

Maximum Pipe Network Pressure 7 bar (-30oC + 70oC)

ENVIRONMENTAL SPECIFICATION

Application Temperature Range -30oC + 70oC

Application Humidity Range 5% to 95% Relative Humidity

PHYSICAL SPECIFICATION

Length	55mm
Weight	11g
Width	30.5mm
Tube Outer Diameter	25mm-27mm
Colour Body	RAL9005 Material ABS
Colour Rubber	Variable material TPE

PART NUMBERS (HARSH ENVIRONMENT VARIANT) - SUPPLIED AS A 5 PACK OF CLIPS

F-PC-HE-2	Pipe Clip Harsh Env 2.0mm (5/64)	Main colour RED
F-PC-HE-2.5	Pipe Clip Harsh Env. 2.5mm (6/64)	Main colour: RED / Tab colour RED
F-PC-HE-3	Pipe Clip Harsh Env. 3.0mm (1/8)	Main colour: ORANGE
F-PC-HE-3.5	Pipe Clip Harsh Env. 3.5mm (9/64)	Main colour: ORANGE / Tab colour ORANGE
F-PC-HE-4	Pipe Clip Harsh Env. 4.0mm (5/32)	Main colour: YELLOW
F-PC-HE-4.5	Pipe Clip Harsh Env. 4.5mm (11/64)	Main colour: YELLOW
F-PC-HE-5	Pipe Clip Harsh Env. 5.0mm (13/64)	Main colour: YELLOW / Tab colour YELLOW
F-PC-HE-5.5	Pipe Clip Harsh Env. 5.5mm (7/32)	Main colour: GREEN
F-PC-HE-6	Pipe Clip Harsh Env. 6.0mm (15/64)	Main colour: GREEN / Tab colour GREEN
F-PC-HE-6.5	Pipe Clip Harsh Env. 6.5mm (1/4)	Main colour: BLUE

**PART NUMBERS (STANDARD VARIANT) -
SUPPLIED AS A 5 PACK OF CLIPS**

F-PC-0	Pipe Clip blind	Main colour BLACK / Tab-colour-Black
F-PC-2	Pipe Clip 2.0mm (5/64)	Main colour: RED
F-PC-2.5	Pipe Clip 2.5mm (6/64)	Main colour: RED / Tab colour RED
F-PC-3	Pipe Clip 3.0mm (1/8)	Main colour: ORANGE
F-PC-3.5	Pipe Clip 3.5mm (9/64)	Main colour: ORANGE / Tab colour ORANGE
F-PC-4	Pipe Clip 4.0mm (5/32)	Main colour: YELLOW
F-PC-4.5	Pipe Clip 4.5mm (11/64)	Main colour: YELLOW / Tab colour YELLOW
F-PC-5	Pipe Clip 5.0mm (13/64)	Main colour: GREEN
F-PC-5.5	Pipe Clip 5.5mm (7/32)	Main colour: GREEN / Tab colour GREEN
F-PC-6	Pipe Clip 6.0mm (15/64)	Main colour: BLUE
F-PC-6.5	Pipe Clip 6.5mm (1/4)	Main colour: BLUE / Tab colour BLUE

For More information

Contact your Business Manager

Honeywell

140 Waterside Road
Hamilton Industrial Estates
Leicester, LE5 1TN
Tel: 0203 409 1779

All technical data is correct at the time of publication and is subject to changes without notice. All trademarks acknowledged. Installation information: In order to ensure full functionality, refer to the installation instructions as supplied.

ASD-CLIPS | 10/19

© 2019 Honeywell International Inc.