

4 Survey

Requested date & time of survey

PPE requirement (list all)

Honeywell will endeavor to schedule the site survey visit within 5 working days of receipt of this form with all accompanying documentation. A site survey will only be carried out if accompanied by a Honeywell partner represent. Where appropriate a Budget kit list may be provided rather than a site survey.

When this first part is completed please return by email to HLSUKsalessupport@honeywell.com

5 Report to be completed by HONEYWELL SECURITY & FIRE

Surveyor`s Name

Organization

Tests Carried out / Customer Requirments / Equipment Location / Survey Notes

When using a HLS-RES-AMP we advise the Antenna is positioned at no less than 2m distance from any area that is open to the General Public to ensure compliance with the 1998 ICNIRP guidelines`

Distance of HLS-RES-AMP Antenna from General Public (m)

Dry Contact Connections: Response Link, Plus & Aid

Below indicates the default messages assigned to each of the 8 dry contacts. Custom messages* can be defined and the unit will be supplied with these as standard.

Default Message:	Alternative Custom Message (max 32 characters)	Contact NO/NC
FIRE, PLEASE EVACUATE		
SECURITY ALARM		
GENERAL ALARM		
LOCKDOWN		
DISABLED REFUGE ACTIVATED		
DISABLED TOILET ALARM		
NURSECALL ACTIVATED		
ACCESS ALARM**		

* If custom message requirements are not supplied the contacts will be programmed with the default messages and normally open.

** Not available on Response Aid

*** For Equality Compliance Act (Formerly DDA) Contact 1 must be NC with default message

**** By default systems that use output control receivers will be set to latched operation unless mono-shot is advised

The following equipment has been identified as being required by the Site Survey.

Part Number:	Description	Qty
HLS-RES-LICENCE	RES. RADIO PAGING LICENCE (5 years)	
HLS-RES-V3AI	RES.AID PAGING SYSTEM	
HLS-RES-V3P	RES.PLUS PAGING SYSTEM	

NB: Vigilon Compact Requires MCB software version 4.47 or above, Part no. VCS-UPG-MCB Nano & Xenex panels are dry contact only

Gent: Ascom protocol (1st Fire Only)

Morley: Port B (all events) or Port D (all events) protocols available, Pager interface 795-067-001 required for ZX Port D Protocol

Notifier: TPP Full Duplex protocol (Fire + 4 events)

SMS: Ascom protocol (1st Fire Only) - SenTRI2 Panel Requires MCB software version 4.47 or above, Part no. VCS-UPG-MCB. SenTRI1 & Conventional panels are dry contact only

Accessories

HLS-RES-AMP	RES. PLUS/AID 25 WATT AMP
HLS-RES-V3REP-PL	RES. REPEATER UHF RX/TX 4 WATTS (Store forward repeater)
HLS-RES-V3REP-AI	RES. WITH BATTERY BACKUP & MONITORING (SFR)
HLS-RES-ANT1	RES. STRAIGHT WIRE ANTENNA
HLS-RES-ANT2	RES. DIPOLE ANTENNA WITH 5M CABLE
HLS-RES-RADIO	RADIO MODULE FOR PLUS AND AID
HLS-RES-SMS	SMS MODULE FOR PLUS AND AID

Paging

HLS-AAPAG-ECA	PAGER AA BATTERY - EQUALITIES COMPLIANCE ACT USE
HLS-AAPAG-FIRE	PAGER AA BATTERY FIRE MARSHALL USE
HLS-RES-PAG-ECA	RECHARGEABLE TFT DISPLAY PAGER - EQUALITIES COMPLIANCE ACT USE (BLACK)
HLS-RES-PAG-FIRE	RECHARGEABLE TFT DISPLAY PAGER FIRE MARSHALL USE (BLACK)
HLS-RES-CHAR15	15 WAY CHARGING RACK (TFT PAGERS)
HLS-RES-WATCH-ECA	WATCH PAGER EQUALITIES COMPLIANCE ACT USE
HLS-RES-WATCH-FIRE	WATCH PAGER FIRE MARSHALL USE

Wireless Call Buttons

HLS-RES-DOORBELL	DOORBELL PAGING TRANSMITTER
HLS-RES-5BUTHAND	5 BUTTON PAGING TRANSMITTER
HLS-RES-SMCKBUT	SMACK BUTTON TWIST PAGING TRANSMITTER
HLS-RES-IP67BUT	IP67 PAGING TRANSMITTER

Spare

HLS-RES-CABLE	RES. RS232 9 PIN CABLE
HLS-RES-PAGBATT	RES. RECHARGEABLE PAGER BATTERY REPLACEMENT
HLS-RES-SK	RES. SYSTEM SURVEY KIT